

Eaton UPS Connectivity Cards: Mini-Slot family

When you combine Eaton® UPSs with Mini-Slot connectivity cards, you can monitor, manage and remotely shutdown UPSs across the network.

For more information on the Mini-Slot family of connectivity cards, please visit powerquality.eaton.com.



Network Card-MS

The Eaton Network Card-MS Web/SNMP Card allows you to connect your Eaton UPS directly to the Ethernet network and the Internet, supporting real-time monitoring and control of UPSs across the network via a standard Web browser, SNMP-compliant network management system or power management software.

Features

- Provides versatile support through HTTP, SNMP, SMTP, Telnet, SSL and SSH compatibility
- Enables remote management of a UPS or rebooting of protected devices over SNMP/Web
- Customizable actions including automatic shutdown in the event of an extended power failure
- Data and event logging
- Receive email/SMS notification of alerts
- Compatible with SNMPv3 and IPv6



Network and MODBUS Card-MS

The Eaton Network and MODBUS Card-MS provides continuous, reliable and accurate remote monitoring of a UPS system through a Building Management System (BMS) or Industrial Automation System (IAS). Enabling data to be integrated from the UPS into a wide variety of management systems, the use of the card allows for supervision of equipment from any network monitoring system using SNMP and traps, or any web browser.

Features

- Facilitates UPS supervision across the network
- Customizable actions including shutdown in the event of an extended power failure
- Data and event logging
- Receive email/SMS notification of alerts
- Temperature/Humidity monitoring through Environment Sensor
- Easy deployment on large installed base



Relay Card-MS

The Eaton Relay Card-MS enables automatic shutdown and network monitoring of UPS system status through a connected computer. A dedicated adapter that provides the essential dry-contact interface between your Eaton UPS and any relay-connected computer as well as a variety of industrial applications, the Relay Card-MS is compatible with all Eaton UPSs that have a Mini-Slot.



Powering Business Worldwide

Technical Specifications

Network - MS & MODBUS - MS	
Protocol support	Fast ETHERNET, 10/100 Mbps, autonegotiation, HTTP 1.1, SNMP V1, SNMP V3, NTP, TFTP, SMTP, BOOTP/DHCP IPv6 Telnet, CLI, SSH, ARP
UPS slot type	Mini-Slot
Network support	Ethernet 10/100BaseT
Temperature and humidity monitoring	Yes
Software support	Intelligent Power® Software Suite, NetWatch, PowerVision, MultiView, any SNMP compliant Network Management System (NMS)
Supported MIB	MIB II - Standard IETF UPS MIB (RFC 1628) - Eaton Pulsar (ex MGE) MIB - Eaton Powerware (PowerMib)
O/S supported for shutdown	Microsoft Windows, UNIX, Linux, NetWare, Macintosh and SuSE (check powerquality.eaton.com for a detailed list of systems supported)
Local language support	English, French, German, Italian, Spanish, Chinese Simplified, Chinese Traditional, Japanese, Russian, Korean, Czech
Operating temperature	32 to 104° F
Operating humidity	90% RH max. without condensation
Power input	5 V - 12 V
Current consumption	300mA max.
Dimensions (HxWxD, in)	5.2 x 2.6 x 1.7
Weight (oz)	2.5
Regulatory	Same as UPS

Relay Card - MS	
Supply voltage	5 V +/- 5%
Supply current (all relays activated)	150 mA max.
Supply current (all relays deactivated)	15 mA max.
Relay contacts (output)	
Double insulation (optocoupler)	>4000V DC
Max. contact resistance	75 mOhm
Max. switching voltage	<40 V AC or <50 V DC
Max. switching current	1 A max (eg. for five contacts, 200 mA max. for each contact)
Max. switching power	40 W
UPS slot type	Mini-Slot

MODBUS - MS

Functions	Parameters	Default values	Possible values
JBUS/MODBUS	Baud rate	9600 baud	1200, 2400, 4800, 9600, 19200 without parity, even parity
	Parity	Without parity	even, odd, none
	Slave number	1	1 to FF (hexadecimal)
	Communication	RS232	RS232, RS485 half duplex (w/ or w/o term.), RS485 full duplex (w/ or w/o term.)

5PX UPS rear view with Network Card-MS



Compatibility of Mini-Slot cards with Eaton UPSs

Network Card-MS

Works with: 5130, 5PX, 9130, 9135, Evolution, Evolution S, EX, MX, MX Frame, EX RT, 9E

Network and MODBUS Card-MS

Works with: 9130, 9135, EX, MX, MX Frame, EX RT, 9E

Relay Card-MS

Works with: 5130, 5PX, 9135, Evolution, Evolution S, EX, MX, MX Frame, EX RT

Eaton Corporation
Electrical Sector
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
powerquality.eaton.com

© 2011 Eaton Corporation
All Rights Reserved
Printed in USA
SFT133FXA / TN
November 2011

EATON
Powering Business Worldwide

Eaton and Intelligent Power are registered trademarks of Eaton Corporation.

All other trademarks are property of their respective owners.